

Material Safety Data Sheet

Butyl Acetate (Sec-) (RXSOL-19-1241-025)



1. Product and Company Identification

Product Name Butyl Acetate (Sec-)

Part Number RXSOL-19-1241-025

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone +91 22 20871200 - 1400

Fax +91 22 27612100 ::AOH :0091 9821214367

Email mail@rxmarine.com

Website www.rxmarine.com

2. Composition / information on ingredients

Chemical Name	CAS	EC number	Weight	Formula
Butyl acetate	123-86-4	204-658-1	= 100 %	C ₆ H ₁₂ O ₂

3. Hazards Identification

Signal Word Warning

Hazard Statements H226 Flammable liquid and vapor. H336 May cause drowsiness or dizziness.

P280 Wear protective gloves. P305 + P351 + P338 Wear eye protection/ face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges.

Classification of the substance or mixture Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

Supplemental Hazard Statements EUH066 Repeated exposure may cause skin dryness or cracking.

Other hazards This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

4. First Aid Measures

General advice Show this material safety data sheet to the doctor in attendance.

If inhaled After inhalation: fresh air. Call in physician.

Eye Contact After eye contact: rinse out with plenty of water. Remove contact lenses.

Swallowed After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

Skin Contact In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

Inhalation Remove patient to fresh air, keep warm and at rest and get medical assistance in necessary.

Ingestion	Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor or Poison Control Center immediately.
Most important symptoms and effects, both acute and delaye	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Indication of any immediate medical attention and special treatment needed	No data available

5. Fire-fighting Measures

Flammability	May be combustible at high temperature.
Flash Point	Higher than 93.3°C (200°F).
Suitable extinguishing media	Carbon dioxide (CO2) Foam Dry powder
Unsuitable extinguishing media	For this substance/mixture no limitations of extinguishing agents are given.
Special hazards arising from the substance or mixture	Carbon oxides Combustible. Vapors are heavier than air and may spread along floors. Forms explosive mixtures with air at elevated temperatures. Development of hazardous combustion gases or vapours possible in the event of fire.
Further information	Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Hazardous combustion products	Fire may cause the evolution of Sulphur oxides, nitrogen oxides.
Advice for firefighters	In the event of fire, wear self-contained breathing apparatus.
Protective Equipment	Use personal protective equipment.
Specific Hazards Arising from the Chemical	Has a fire-promoting effect due to the release of oxygen. Ambient fire may liberate hazardous vapours.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.
Spillage	Oxidizing material. Stop leak if without risk. Avoid contact with a combustible material (wood, paper, oil, clothing...). Keep substance damp using water spray. Do not touch spilled material. Prevent entry into sewers, basements or confined areas dike if needed. Eliminate all ignition sources. Call for assistance on disposal.
Personal Protection	Advice for non-emergency personnel: Avoid inhalation of dusts. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: Protective equipment see section 8.
Enviromental Precaution	Do not let product enter drains. Risk of explosion.
Methods and materials for containment and cleaning	Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

7. Handling and Storage

Advice on safe handling	Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.
Advice on protection against fire and explosion	Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.
Incompatible materials	Keep away from alkalis, strong oxidizing agents and metals. Provide containment walls of adequate capacity to hold any accidental spills.
Hygiene measures	Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance. For precautions see section 2.2.
Storage conditions	Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.
Storage class	Storage class (TRGS 510): 3: Flammable liquids
Specific end use(s)	Apart from the uses mentioned in section 1.2 no other specific uses are stipulated
Advice on general occupational hygiene	Advice on safe handling Observe label precautions. Change contaminated clothing. Wash hands after working with substance.
Requirements for storage	Keep in cool and store under shade.

8. Exposure controls and personal protection

Application Area	Routes of exposure	Health effect	Value
Worker DNEL, acute	Inhalation	Local effects	600 mg/m3
Worker DNEL, acute	Inhalation	Systemic effects	600 mg/m3
Worker DNEL, longterm	Inhalation	Local effects	300 mg/m3
Worker DNEL, longterm	Inhalation	Systemic effects	300 mg/m3
Consumer DNEL, acute	Inhalation	Local effects	300 mg/m3

Predicted No Effect Concentration (PNEC)

Compartment	Value
Sea water	0,018 mg/l
Fresh water	0,18 mg/l
Sewage treatment plant	35,6 mg/l
Aquatic intermittent release	0,36 mg/l

Exposure controls	No specific additional engineering controls are required. Provide good natural or artificial ventilation.
Engineering Control	Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.
Eye/face protection	Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses
Body Protection	Flame retardant antistatic protective clothing.
Skin protection	This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Full contact Material: Nitrile rubber Minimum layer thickness: 0,11 mm Break through time: 480 min Material tested:KCL 741 Dermatril® L This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Splash contact Material: Nitrile rubber Minimum layer thickness: 0,11 mm Break through time: 480 min Material tested:KCL 741Dermatril®L
Respiratory protection	Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.
Other Protection Measure	Handle in accordance with good industrial hygiene and safety practice.
Control of environmental exposure	Do not let product enter drains. Risk of explosion.
Thermal hazards	No data available

9. Physical and chemical properties

Physical state	Liquid
Colour	Colorless, clear
Odour	Fruity
Odor Threshold	Not Applicable
pH	6,2 at 5,3 g/l at 20 °C
Melting Point	-78 °C - lit.
Boiling Point	124 - 126 °C - lit.
Flash Point	27 °C - closed cup
Evaporation Rate	Not Applicable
Flammability (solid, gas)	No data available
Explosive limits	No Data Available
Upper/lower flammability or explosive limits	7,6 %(V)/1,7 %(V)

Autoignition temperature	415 °C at 1.010 hPa - DIN 51794
Decomposition temperature	No data available
Vapour pressure	11,2 hPa at 20 °C
Viscosity /kinematic / dynamic	0,83 mm ² /s at 20 °C / 0,73 mPa.s at 20 °C
Density	0,88 g/cm ³ at 25 °C - lit.
Relative Vapour Density	4,01 - (Air = 1.0)
Freezing point	No data available
Specific Gravity	No data available
Partition coefficient	log Pow: 2,3 at 25 °C
Explosive properties	No data available
Solubility	5,3 g/l at 20 °C
Ignition temperature	No information available.
Particle characteristics	No data available

10. Stability and reactivity

Reactivity	Vapor/air-mixtures are explosive at intense warming.
Stability	The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	Risk of explosion with: Alkali metals alkali hydroxides Strong oxidizing agents
Conditions to avoid	Heating.
Incompatible materials	Rubber, various plastics
Hazardous Polymerization	In the event of fire: see section 5

11. Toxicological information

Acute toxicity	LD50 Oral - Rat - female - 10.760 mg/kg (OECD Test Guideline 423) Symptoms: Risk of aspiration upon vomiting., Aspiration may cause pulmonary edema and pneumonitis. Inhalation: No data available LD50 Dermal - Rabbit - male and female - 14.112 mg/kg (OECD Test Guideline 402)
Skin corrosion/irritation	Skin - Rabbit Result: No skin irritation - 4 h (OECD Test Guideline 404) Remarks: Drying-out effect resulting in rough and chapped skin.
Serious eye damage/eye irritation	Eyes - Rabbit Result: No eye irritation (OECD Test Guideline 405)
Respiratory or skin sensitization	No data available
Toxicity to Animal	WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE Acute oral toxicity (LD50): 689 mg/kg [Rat].
Toxic Effects on Human	May cause damage to the following organs: upper respiratory tract. Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant, sensitizer), of ingestion, of inhalation (lung irritant, lung sensitizer).
Carcinogenicity	This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.
Germ cell mutagenicity	Test Type: Ames test Test system: Escherichia coli/Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative Test Type: Micronucleus test Species: Mouse Cell type: Red blood cells (erythrocytes) Application Route: Oral Method: OECD Test Guideline 474 Result: negative
Reproductive toxicity	No data available
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness. - Central nervous system
Special Remarks on other Toxi Effects on Humans	Acute Potential Health Effects: Skin: Causes skin irritation. May cause skin sensitization, an allergic reaction, which becomes evident upon re-exposure to this material. Eyes: Causes eye irritation. Ingestion: Causes gastrointestinal (digestive) tract irritation with nausea, vomiting, and diarrhea. May be harmful if swallowed. Inhalation: Causes respiratory tract irritation. May cause chemical pneumonitis and pulmonary edema, inflammation, edema of bronchi and larynx. Chronic Potential Health Effects: Repeated or prolonged skin exposure may cause allergic reactions in sensitive individuals. Repeated or prolonged exposure by inhalation may affect respiration and metabolism.
Additional Information	RTECS: AF3675000 Gastrointestinal disturbance To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. After uptake of large quantities: muscular symptoms agitation Convulsions Headache Tremors Nausea psychoses

Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Repeated dose toxicity - Rat - male and female - Oral - 13 Weeks - NOAEL (No observed adverse effect level) - 125 mg/kg - LOAEL (Lowest observed adverse effect level) - 500 mg/kg RTECS: AF7350000 Drowsiness To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. After absorption of large quantities: somnolence Drowsiness narcosis Handle in accordance with good industrial hygiene and safety practice.

12. Ecological information

Persistence and degradability	Biodegradability aerobic - Exposure time 28 d Result: 83 % - Readily biodegradable. (OECD Test Guideline 301D) Theoretical oxygen demand 2.207 mg/g Remarks: (Lit.) Ratio BOD/ThBOD 7 - 46 % Remarks: (Lit.)
Toxicity to fish	Flow-through test LC50 - Pimephales promelas (fathead minnow) - 18 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	Static test EC50 - Daphnia magna (Water flea) - 44 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae	Static test ErC50 - Pseudokirchneriella subcapitata (green algae) - 397 mg/l - 72 h (OECD Test Guideline 201) Remarks: (in analogy to similar products) The value is given in analogy to the following substances: Isobutyl acetate
Toxicity to bacteria	Static test IC50 - Tetrahymena pyriformis - 356 mg/l - 40 h Remarks: (ECHA)
Mobility in soil	No Information available
Results of PBT and vPvB assessment	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
Endocrine disrupting properties	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Other adverse effects	Discharge into the environment must be avoided.

13. Disposal considerations

Disposal methods	The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.
Contaminated packaging	Containers can be triply rinsed (or equivalent) and offered for recycling or reconditioning. Alternatively, the packaging can be punctured to make it unusable for other purposes and then be disposed of in a sanitary landfill. Controlled incineration with flue gas scrubbing is possible for combustible packaging materials.
Waste treatment Method	See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

14. Transport information

UN number	ADR/RID: 1123 IMDG: 1123 IATA: 1123
UN proper shipping name	ADR/RID: BUTYL ACETATES IMDG: BUTYL ACETATES IATA: BUTYL ACETATES
Transport hazard class(es)	ADR/RID: 3 IMDG: 3 IATA: 3
Packaging group	ADR/RID: III IMDG: III IATA: III
Environmental hazards	ADR/RID: No IMDG: No IATA: No
Special precautions for user	Tunnel restriction code : (C/E)
Further information	Not classified as dangerous in the meaning of transport regulations.
Transport in bulk according to IMO instruments	No data available

15. Regulatory information

Inventory status	Components are on the following inventories: Polymaleic acid: - US TSCA, Canadian DSL, EU EINECS, Australian AICS, Korean, Philippine PICCS and Chinese Xi irritant R 36/38 Irritant to eyes & skin R 41 Risk of serious damage to eyes S24/25 Avoid contact with skin and eyes S26/28 In case of contact eyes & skin, rinse with plenty water and seek medical advice Section 312/313: Not listed. Not listed under California proposition 65.
------------------	---

Safety, health and environmental regulations/legislation specific for the substance or mixture	This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
Safety, health and environmental regulations specific for the product in question	European Inventory of Existing Commercial Chemical Substances (EINECS) -Listed. EC Inventory Listed. United States Toxic Substances Control Act (TSCA) Inventory- Listed. China Catalog of Hazardous chemicals 2015 Not- Listed. New Zealand Inventory of Chemicals (NZIoC) Listed. PICCS -Listed. Vietnam National Chemical Inventory -Listed. IECSC Listed. Korea Existing Chemicals List (KECL) - Listed.
National legislation	Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : FLAMMABLE LIQUIDS
Other regulations	Take note of Dir 94/33/EC on the protection of young people at work.
Chemical Safety Assessment	A Chemical Safety Assessment has been carried out for this substance.

16. Other information

Other Information	The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages. DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.
-------------------	--