

Material Safety Data Sheet

DI ISOPROPANOL AMINE (RXSOL-19-1136-025)



1. Product and Company Identification

Product Name DI ISOPROPANOL AMINE

Part Number RXSOL-19-1136-025

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone +91 22 20871200 - 1400

Fax +91 22 27612100 ::::AOH :0091 9821214367

Email mail@rxmarine.com

Website www.rxmarine.com

2. Composition / information on ingredients

Chemical Name	CAS	EC number	Weight	Formula
Diisopropylamine	108-18-9	203-558-5	= 100 %	C ₆ H ₁₅ N

3. Hazards Identification

Signal Word Danger

Hazard Statements H225 Highly flammable liquid and vapor. H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H331 Toxic if inhaled. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Classification of the substance or mixture Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

Supplemental Hazard Statements None.

Other hazards This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. Lachrymator., Rapidly absorbed through skin. .

4. First Aid Measures

General advice First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

Eye Contact After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

Swallowed After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

Skin Contact	In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician immediately.
Inhalation	Remove patient to fresh air, keep warm and at rest and get medical assistance in necessary.
Ingestion	Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor or Poison Control Center immediately.
Most important symptoms and effects, both acute and delaye	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Indication of any immediate medical attention and special treatment needed	No data available

5. Fire-fighting Measures

Flammability	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Suitable extinguishing media	Carbon dioxide (CO2) Foam Dry powder
Unsuitable extinguishing media	For this substance/mixture no limitations of extinguishing agents are given.
Special hazards arising from the substance or mixture	Carbon oxides Nitrogen oxides (NOx) Flash back possible over considerable distance., Container explosion may occur under fire conditions. Combustible. Pay attention to flashback. Vapors are heavier than air and may spread along floors. Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.
Further information	Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Hazardous combustion products	Fire may cause the evolution of Sulphur oxides, nitrogen oxides.
Advice for firefighters	Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.
Protective Equipment	Use personal protective equipment.
Specific Hazards Arising from the Chemical	Oxides of phosphorus Sodium oxides Not combustible. Fire may cause evolution of: Oxides of phosphorus Ambient fire may liberate hazardous vapours.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.
Spillage	Oxidizing material. Stop leak if without risk. Avoid contact with a combustible material (wood, paper, oil, clothing...). Keep substance damp using water spray. Do not touch spilled material. Prevent entry into sewers, basements or confined areas dike if needed. Eliminate all ignition sources. Call for assistance on disposal.
Enviromental Precaution	Do not let product enter drains. Risk of explosion.
Methods and materials for containment and cleaning	Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

7. Handling and Storage

Advice on protection against fire and explosion	Keep away from open flames, hot surfaces and sources of ignition.Take precautionary measures against static discharge.
Incompatible materials	Keep away from alkalis, strong oxidizing agents and metals. Provide containment walls of adequate capacity to hold any accidental spills.
Hygiene measures	Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.
Precautions for safe handling	For precautions see section 2.2.
Storage conditions	Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.
Storage class	Storage class (TRGS 510): 3: Flammable liquids
Specific end use(s)	Apart from the uses mentioned in section 1.2 no other specific uses are stipulated
Advice on general occupational hygiene	Advice on safe handling Observe label precautions. Change contaminated clothing. Wash hands after working with substance.

8. Exposure controls and personal protection

Exposure controls	Appropriate engineering controls Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Control parameters	Ingredients with workplace control parameters Contains no substances with occupational exposure limit values.
Engineering Control	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Eye/face protection	Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles
Body Protection	Flame retardant antistatic protective clothing.
Skin protection	This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Full contact Material: Nitrile rubber Minimum layer thickness: 0,4 mm Break through time: 480 min Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M) This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Splash contact Material: butyl-rubber Minimum layer thickness: 0,7 mm Break through time: 30 min Material tested: Butoject® (KCL 898)
Respiratory protection	Required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system. Recommended Filter type: Filter type ABEK The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.
Other Protection Measure	Handle in accordance with good industrial hygiene and safety practice.
Control of environmental exposure	Do not let product enter drains. Risk of explosion.

9. Physical and chemical properties

Physical state	Liquid
Colour	Colorless
Odour	Amine-like
Odor Threshold	No data available
pH	11,8 at 6 g/l at 20 °C
Melting Point	-61 °C
Boiling Point	84 °C
Flash Point	13,45 °C - closed cup
Evaporation Rate	Not Applicable
Flammability (solid, gas)	No data available
Explosive limits	No Data Available
Upper/lower flammability or explosive limits	7,1 %(V) / 1,1 %(V)
Autoignition temperature	295 °C at 1.007 hPa
Decomposition temperature	No data available
Vapour pressure	93,33 hPa at 20 °C
Density	0,722 g/mL at 25 °C
Relative Density	No data available
Relative vapor density	3,5
Freezing point	No data available
Viscosity dynamic	0,4 mPa.s at 25 °C
Partition coefficient	log Pow: -0,72 at 20 °C
Explosive properties	No data available

Solubility	20 °C
Ignition temperature	No information available.
Particle characteristics	No data available

10. Stability and reactivity

Reactivity	Vapors may form explosive mixture with air.
Stability	The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	Risk of ignition or formation of inflammable gases or vapours with: Strong oxidizing agents nitrates perchlorates Aluminum Peroxides Exothermic reaction with: halogens acids Caution! In contact with nitrites, nitrates, nitrous acid possible liberation of nitrosamines!
Conditions to avoid	Warming.
Incompatible materials	Aluminum
Hazardous decomposition products	In the event of fire: see section 5

11. Toxicological information

Acute toxicity	LD50 Oral - Rat - male and female - 420 mg/kg (US-EPA) Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach. Acute toxicity estimate Oral - 420 mg/kg (Calculation method) LC50 Inhalation - Rat - male and female - 4 h - 5,35 mg/l - vapor (OECD Test Guideline 403) Symptoms: mucosal irritations, Cough, Shortness of breath, Lung edema, Possible damages:, damage of respiratory tract Acute toxicity estimate Inhalation - 5,35 mg/l - vapor (Calculation method) LD50 Dermal - Rat - male and female - > 2.000 - 5.000 mg/kg (OECD Test Guideline 402)
Skin corrosion/irritation	Skin - Rabbit Result: Causes burns. - 3 min (OECD Test Guideline 404)
Serious eye damage/eye irritation	Eyes - Rabbit Result: Causes burns. (OECD Test Guideline 405) Remarks: Causes serious eye damage. Remarks: conjunctivitis
Respiratory or skin sensitization	Maximization Test - Guinea pig Result: negative (OECD Test Guideline 406)
Toxic Effects on Human	May cause damage to the following organs: upper respiratory tract. Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant, sensitizer), of ingestion, of inhalation (lung irritant, lung sensitizer).
Carcinogenicity	Suspected of causing cancer.
Germ cell mutagenicity	Test Type: In vitro mammalian cell gene mutation test Test system: Mouse lymphoma test Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476 Result: negative Test Type: Mutagenicity (mammal cell test): chromosome aberration. Test system: Human lymphocytes Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 473 Result: negative Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative
Reproductive toxicity	No data available
Specific target organ toxicity - single exposure	No data available
Special Remarks on other Toxic Effects on Humans	Acute Potential Health Effects: Skin: Causes skin irritation. May cause skin sensitization, an allergic reaction, which becomes evident upon re-exposure to this material. Eyes: Causes eye irritation. Ingestion: Causes gastrointestinal (digestive) tract irritation with nausea, vomiting, and diarrhea. May be harmful if swallowed. Inhalation: Causes respiratory tract irritation. May cause chemical pneumonitis and pulmonary edema, inflammation, edema of bronchi and larynx. Chronic Potential Health Effects: Repeated or prolonged skin exposure may cause allergic reactions in sensitive individuals. Repeated or prolonged exposure by inhalation may affect respiration and metabolism.
Endocrine disrupting properties	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Repeated dose toxicity - Rat - male and female - Oral - 33 Days - NOAEL (No observed adverse effect level) - 15 mg/kg Remarks: (ECHA) Repeated dose toxicity - Rat - male and female - Dermal - 28 d - NOAEL (No observed adverse effect level) - >= 150 mg/kg RTECS: IM4025000 burning sensation, Cough, wheezing, laryngitis, Shortness of breath, spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Systemic effects: After absorption: Headache Convulsions CNS disorders Under given conditions, contact with nitrites or nitric acid can lead to the formation of nitrosamines, which have shown themselves to be carcinogenic in animal experiments. Other dangerous properties can not be excluded. Handle in accordance with good industrial hygiene and safety practice. Liver - Irregularities - Based on Human Evidence .

12. Ecological information

Bioaccumulative potential	No data available
Persistence and degradability	Biodegradability aerobic - Exposure time 28 d Result: 11 % - Not readily biodegradable. (OECD Test Guideline 301D)
Toxicity to fish	Static test LC50 - Leuciscus idus (Golden orfe) - 26 mg/l - 96 h (DIN 38412 part 15)
Toxicity to daphnia and other aquatic invertebrates	Static test LC50 - Daphnia magna (Water flea) - 110 mg/l - 48 h Remarks: (ECHA)
Toxicity to algae	Static test EC50 - SELENASTRUM - 20 mg/l - 96 h (US-EPA)
Toxicity to bacteria	Static test EC50 - activated sludge - > 100 mg/l - 3 h (OECD Test Guideline 209)
Mobility in soil	No Information available
Results of PBT and vPvB assessment	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
Endocrine disrupting properties	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Other adverse effects	No data available

13. Disposal considerations

Disposal methods	The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.
Contaminated packaging	Dispose of as unused product.
Waste treatment Method	See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

14. Transport information

UN number	ADR/RID:1158	IMDG:1158	IATA: 1158
	ADR/RID:Diisopropylamine		
UN proper shipping name	IMDG: Diisopropylamine		
	IATA:Diisopropylamine		
Transport hazard class(es)	ADR/RID:3 (8)	IMDG: 3 (8)	IATA:3 (8)
Packaging group	ADR/RID: II	IMDG: II	IATA: II
Environmental hazards	ADR/RID: NO	IMDG: NO	IATA: NO
Further information	No data available		

15. Regulatory information

Inventory status	Components are on the following inventories: Polymaleic acid: - US TSCA, Canadian DSL, EU EINECS, Australian AICS, Korean, Philippine PICCS and Chinese Xi irritant R 36/38 Irritant to eyes & skin R 41 Risk of serious damage to eyes S24/25 Avoid contact with skin and eyes S26/28 In case of contact eyes & skin, rinse with plenty water and seek medical advice Section 312/313: Not listed. Not listed under California proposition 65.
Safety, health and environmental regulations/legislation specific for the substance or mixture	This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
National legislation	Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : ACUTE TOXIC : FLAMMABLE LIQUIDS
Other regulations	Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable. Take note of Dir 94/33/EC on the protection of young people at work.

16. Other information

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages.

Other Information

DISCLAIMER OF LIABILITY : The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.