

Material Safety Data Sheet

ISOBUTYL ACETATE (RXSOL-19-1326-025)



1. Product and Company Identification

Product Name RXSOL-19-1326
Product Type ISOBUTYL ACETATE

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone +91 22 65113333 / 5555 / 9999 / 27815540
Fax +91 22 2781 1318 ::AOH :0091 9821214367
Email mail@rxmarine.com
Website www.rxmarine.com

2. Composition / information on ingredients

Chemical Name	CAS Number	EC Number	Index number
isobutyl acetate	110-19-0	203-745-1	607-026-00-7

3. Hazards Identification

Hazard description:

Information concerning particular hazards for human and environment:

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

R 11 Highly flammable.

R 66 Repeated exposure may cause skin dryness or cracking.

4. First Aid Measures

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact Generally the product does not irritate the skin.

After eye contact Rinse opened eye for several minutes under running water.

After swallowing If symptoms persist consult doctor.

5. Fire-fighting Measures

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

Protective equipment: No special measures required.

6. Accidental Release Measures

Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.

Measures for environmental protection: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

Measures for cleaning/collecting: Dilute with plenty of water. Ensure adequate ventilation.

7. Handling and Storage

Handling:

Information for safe handling: Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

8. Exposure controls and personal protection

Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

110-19-0 isobutyl acetate

PEL (USA)

700 mg/m³, 150 ppm

REL (USA)

700 mg/m³, 150 ppm

TLV (USA)

713 mg/m³, 150 ppm

WEL (Great Britain)

Short-term value: 903 mg/m³, 187 ppm

Long-term value: 724 mg/m³, 150 ppm

Additional information: The lists valid during the making were used as basis.

Personal protective equipment:

General protective and hygienic measures: Wash hands before breaks and at the end of work.

Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves: The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed goggles

9. Physical and chemical properties

General Information

Form

Fluid

Colour

Colourless

Odour

Fruit-like

Change in condition

Melting point/Melting range	-98.85°C
Boiling point/Boiling range	117.2°C
Flash point	18°C
Ignition temperature	405°C
Danger of explosion	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower	2.4 Vol %
Upper	10.5 Vol %
Vapour pressure at 20°C	20 hPa
Density at 20°C	0.8747 g/cm ³
Solubility in / Miscibility with water at 20°C	7 g/l
pH-value (4 g/l) at 20°C	6
Viscosity:	
Dynamic	0.96 mPas

10. Stability and reactivity

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Dangerous reactions No dangerous reactions known.

Dangerous decomposition products: No dangerous decomposition products known.

11. Toxicological information

Acute toxicity:

LD/LC50 values relevant for classification:

Oral	LD50	13400 mg/kg (rat)
------	------	-------------------

Primary irritant effect:

on the skin	No irritant effect.
on the eye	No irritating effect.
Sensitization	No sensitizing effects known.

12. Ecological information

General notes: Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13. Disposal considerations

Product:

Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging: Recommendation: Disposal must be made according to official regulations.

14. Transport information

Land transport ADR/RID (cross-border)

ADR/RID class	3 Flammable liquids.
Danger code (Kemler)	33

UN-Number	1213
Packaging group	II
Hazard label	3
Description of goods	1213 ISOBUTYL ACETATE

Maritime transport IMDG

IMDG Class	3
UN Number	1213
Label	3
Packaging group	II
EMS Number	F-E,S-D
Marine pollutant	No
Proper shipping name	ISOBUTYL ACETATE

Air transport ICAO-TI and IATA-DGR

ICAO/IATA Class	3
UN/ID Number	1213
Label	3
Packaging group	II
Proper shipping name	ISOBUTYL ACETATE

15. Regulatory information

Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

Risk phrases:

- 11 Highly flammable.
- 66 Repeated exposure may cause skin dryness or cracking.

Safety phrases:

- 2 Keep out of the reach of children.
- 16 Keep away from sources of ignition - No smoking.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 25 Avoid contact with eyes.

16. Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

DISCLAIMER OF LIABILITY : The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.