

Material Safety Data Sheet

Chlorine Liquid (RXSOL-40-3038-210)



1. Product and Company Identification

Product Name Chlorine Liquid FG
Part Number RXSOL-40-3038-210

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone +91 22 20871200 - 1400
Fax +91 22 27612100 ::AOH :0091 9821214367
Email mail@rxmarine.com
Website www.rxmarine.com

2. Composition / information on ingredients

Chemical Name	CAS	EC number
Chlorine Liq	7782-50-5	231-959-5

3. Hazards Identification

Signal Word Danger

Hazard Statements H270 May cause or intensify fire; oxidizer. H280 Contains gas under pressure; may explode if heated. H315 Causes skin irritation. H319 Causes serious eye irritation. H330 Fatal if inhaled. H335 May cause respiratory irritation. H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements P273 Avoid release to the environment. P302 + P352 IF ON SKIN: Wash with plenty of water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Classification of the substance or mixture Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

Supplemental Hazard Statements None.

Other hazards This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. Contact with liquid or refrigerated gas can cause cold burns and frostbite.

4. First Aid Measures

General advice First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

Eye Contact After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

Swallowed After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

Skin Contact In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

Inhalation	Remove patient to fresh air, keep warm and at rest and get medical assistance in necessary.
Ingestion	Rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a doctor or Poison Control Center immediately.
Most important symptoms and effects, both acute and delaye	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Indication of any immediate medical attention and special treatment needed	Note for the doctor: It is recommended to consult a doctor with experience in the treatment of lesions caused by hydrofluoric acid. If a systemic effect is suspected, monitoring and treatment in an intensive care unit is urgently required. Caution, ventricular fibrillation due to electrolyte imbalance.

5. Fire-fighting Measures

Flammability	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Flash Point	Dry powder Dry sand
Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	For this substance/mixture no limitations of extinguishing agents are given.
Special hazards arising from the substance or mixture	Hydrogen chloride gas Not combustible. Has a fire-promoting effect due to release of oxygen. Ambient fire may liberate hazardous vapours.
Further information	Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Hazardous combustion products	Fire may cause the evolution of Sulphur oxides, nitrogen oxides.
Advice for firefighters	Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.
Protective Equipment	Use personal protective equipment.
Specific Hazards Arising from the Chemical	Oxides of phosphorus Sodium oxides Not combustible. Fire may cause evolution of: Oxides of phosphorus Ambient fire may liberate hazardous vapours.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Advice for non-emergency personnel: Do not breathe gas. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.
Spillage	Oxidizing material. Stop leak if without risk. Avoid contact with a combustible material (wood, paper, oil, clothing...). Keep substance damp using water spray. Do not touch spilled material. Prevent entry into sewers, basements or confined areas dike if needed. Eliminate all ignition sources. Call for assistance on disposal.
Enviromental Precaution	Do not let product enter drains.
Methods and materials for containment and cleaning	Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Stop flow of gas, move leaking cylinder to open air if without risk.

7. Handling and Storage

Advice on safe handling	Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.
Advice on protection against fire and explosion	Provide appropriate exhaust ventilation at places where dust is formed.
Incompatible materials	Keep away from alkalis, strong oxidizing agents and metals. Provide containment walls of adequate capacity to hold any accidental spills.
Hygiene measures	Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.
Precautions for safe handling	For precautions see section 2.2.
Storage conditions	Tightly closed. Keep locked up or in an area accessible only to qualified or authorized persons. Keep away from combustible materials and sources of ignition. Contents under pressure.
Storage class	Storage class (TRGS 510): 2A: Gases
Specific end use(s)	Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

Handling	Keep away from heat. Keep away from sources of ignition. Keep away from combustible material.. Empty containers pose a fire risk, evaporate the residue under a fume hood. Ground all equipment containing material. Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as reducing agents, combustible materials, organic materials, metals
Advice on general occupational hygiene	Advice on safe handling Observe label precautions. Change contaminated clothing. Wash hands after working with substance.
Requirements for storage	Keep in cool and store under shade.

8. Exposure controls and personal protection

Exposure controls	Appropriate engineering controls Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Control parameters	Ingredients with workplace control parameters Contains no substances with occupational exposure limit values.
Engineering Control	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Eye/face protection	Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses
Body Protection	Protective clothing.
Skin protection	This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Full contact Material: Viton® Minimum layer thickness: 0,7 mm Break through time: 480 min Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M) This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Splash contact Material: Viton® Minimum layer thickness: 0,7 mm Break through time: 480 min Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)
Respiratory protection	Recommended Filter type: Filter B-(P3) The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.
Other Protection Measure	Handle in accordance with good industrial hygiene and safety practice.
Control of environmental exposure	Do not let product enter drains.

9. Physical and chemical properties

Physical state	Liquid
Colour	Yellow
Odour	Pungent
Odor Threshold	No data available
pH	1,8 at 6,4 g/l at 20 °C
Melting Point	101 °C - lit.
Boiling Point	34 °C - lit.
Flash Point	No data available
Evaporation Rate	Not Applicable
Flammability (solid, gas)	No data available
Explosive limits	No Data Available
Upper/lower flammability or explosive limits	No data available
Autoignition temperature	No data available
Decomposition temperature	No data available
Vapour pressure	6.399 hPa at 20 °C
Density	1,4 g/cm3 at 20 °C at 6.946,09 hPa

Relative Density	No data available
Relative vapor density	2,44 - (Air = 1.0)
Freezing point	No data available
Viscosity	Dynamic: 12,4 mPa.s at 0 °C 13,3 mPa.s at 20 °C
Partition coefficient	No data available
Explosive properties	No data available
Solubility	7,41 g/l at 20 °C
Ignition temperature	No information available.
Particle characteristics	No data available

10. Stability and reactivity

Reactivity	No data available
Stability	The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	Risk of ignition or formation of inflammable gases or vapours with: Copper Risk of explosion with: Hydrogen Acetylene Ammonia Metals Aluminum Tin Mild steel Iron phosphorus Violent reactions possible with: numerous inorganic and/or organic compounds Water Oxygen acids
Conditions to avoid	No data available
Incompatible materials	Bronze
Hazardous decomposition products	In the event of fire: see section 5

11. Toxicological information

Acute toxicity	Oral: No data available LC50 Inhalation - Rat - male and female - 4 h - 0,2 mg/l - vapor (OECD Test Guideline 403) Symptoms: damage of respiratory tract, Cough, Shortness of breath LD50 Dermal - Rabbit - male and female - > 20.000 mg/kg (OECD Test Guideline 402) The value is given in analogy to the following substances: sodium hypochlorite solution
Skin corrosion/irritation	Skin - Rabbit Result: Irritating to skin. - 4 h (OECD Test Guideline 404) Remarks: (in analogy to similar products) The value is given in analogy to the following substances: sodium hypochlorite solution Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)
Serious eye damage/eye irritation	Remarks: Causes serious eye irritation. Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)
Respiratory or skin sensitization	Buehler Test - Guinea pig Result: negative (OECD Test Guideline 406) Remarks: (in analogy to similar products) The value is given in analogy to the following substances: sodium hypochlorite solution
Toxic Effects on Human	May cause damage to the following organs: upper respiratory tract. Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant, sensitizer), of ingestion, of inhalation (lung irritant, lung sensitizer).
Carcinogenicity	This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.
Germ cell mutagenicity	No data available
Reproductive toxicity	No data available
Specific target organ toxicity - single exposure	Inhalation - May cause respiratory irritation. - Respiratory Tract Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)
Special Remarks on other Toxi Effects on Humans	Acute Potential Health Effects: Skin: Causes skin irritation. May cause skin sensitization, an allergic reation, which becomes evident upon re-exposure to this material. Eyes: Causes eye irritation. Ingestion: Causes gastrointestinal (digestive) tract irritation with nausea, vomiting, and diarrhea. May be harmful if swallowed. Inhalation: Causes respiratory tract irritation. May cause chemical pneumonitis and pulmonary edema, inflammation, edema of bronchi and larynx. Chronic Potential Health Effects: Repeated or prolonged skin exposure may cause allergic reactions in sensitive individuals. Repeated or prolonged exposure by inhalation may affect respiration and metabolism.

Endocrine disrupting properties	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Repeated dose toxicity - Rat - male - Oral - 90 Days - NOAEL (No observed adverse effect level) - >= 16,7 mg/kg - LOAEL (Lowest observed adverse effect level) - > 16,7 mg/kg Remarks: (in analogy to similar products) The value is given in analogy to the following substances: sodium hypochlorite solution RTECS: FO2100000 Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., Cough, Shortness of breath, Headache, Nausea To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Possible damages: in case of perspiration/moisture corrosive. After long-term exposure to the chemical: Cyanosis Lung edema Vomiting Circulatory collapse The substance has delayed effects. In high concentrations: respiratory arrest Handle in accordance with good industrial hygiene and safety practice.
---------------------------------	--

12. Ecological information

Bioaccumulative potential	No data available
Persistence and degradability	The methods for determining biodegradability are not applicable to inorganic substances. Theoretical oxygen demand 0 - 230 mg/g Remarks: (calculated)(IUCLID)
Toxicity to fish	Flow-through test LC50 - <i>Leistomus xanthurus</i> - 0,09 mg/l - 96 h Remarks: (in analogy to similar products) (ECHA)
Toxicity to daphnia and other aquatic invertebrates	Flow-through test EC50 - <i>Ceriodaphnia dubia</i> (water flea) - 0,035 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae	Flow-through test NOEC - algae - 0,002 mg/l - 7 Days Remarks: (in analogy to similar products) (ECHA) The value is given in analogy to the following substances: sodium hypochlorite solution
Toxicity to bacteria	Static test EC50 - activated sludge - 563 mg/l - 3 h (OECD Test Guideline 209) Remarks: (in analogy to similar products) The value is given in analogy to the following substances: sodium hypochlorite solution
Mobility in soil	No Information available
Results of PBT and vPvB assessment	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
Endocrine disrupting properties	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Other adverse effects	Biological effects: Forms toxic mixtures in water, dilution measures notwithstanding. Discharge into the environment must be avoided.

13. Disposal considerations

Disposal methods	The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.
Contaminated packaging	Dispose of as unused product.
Waste treatment Method	Pressurised gas bottle: dispose of only in empty condition! See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

14. Transport information

UN number	ADR/RID:1017	IMDG: 1017	IATA:1017
UN proper shipping name	ADR/RID:CHLORINE	IMDG:CHLORINE	IATA: CHLORINE
Transport hazard class(es)	ADR/RID:2.3 (5.1, 8)	IMDG: 2.3 (5.1, 8)	IATA: 2.3 (5.1, 8)
Packaging group	ADR/RID: IMDG: IATA:		
Environmental hazards	ADR/RID: yes	IMDG: yes	IATA: NO
Further information	No data available		

15. Regulatory information

Inventory status	Components are on the following inventories: Polymaleic acid: - US TSCA, Canadian DSL, EU EINECS, Australian AICS, Korean, Philippine PICCS and Chinese Xi irritant R 36/38 Irritant to eyes & skin R 41 Risk of serious damage to eyes S24/25 Avoid contact with skin and eyes S26/28 In case of contact eyes & skin, rinse with plenty water and seek medical advice Section 312/313: Not listed. Not listed under California proposition 65.
------------------	---

Safety, health and environmental regulations/legislation specific for the substance or mixture	This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Restrictions on the marketing and use of certain dangerous substances : Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).
Authorisations and/or restrictions on use	REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : potassium chromate This product contains a substance listed on Annex XIV of the REACH Regulation (EC) Nr. 1907/2006. Listed substance / Sunset Date : potassium chromate / 21.09.2017 After the sunset date the use of this substance requires either an authorization or can only be used for exempted uses, e.g. use in scientific research and development which includes routine analytics or use as intermediate.REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : potassium chromate
National legislation	Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous : ACUTE TOXIC substances. : OXIDISING GASES : ENVIRONMENTAL HAZARDS : Chlorine
Other regulations	Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable. Take note of Dir 94/33/EC on the protection of young people at work.
Chemical Safety Assessment	For this product a chemical safety assessment was not carried out

16. Other information

Other Information	The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages. DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.
-------------------	--