

Material Safety Data Sheet

CARBOLIC ACID (RXSOL-19-1910-225)



1. Product and Company Identification

Product Name CARBOLIC ACID
Part Number RXSOL-19-1910-025

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone +91 22 20871200 - 1400
Fax +91 22 27612100 ::AOH :0091 9821214367
Email mail@rxmarine.com
Website www.rxmarine.com

2. Composition / information on ingredients

Chemical Name		Cas No	EC No	Whight	Formula
Hydroxybenzene		108-95-2	203-632-7	94,11 g/mol	C ₆ H ₆ O
Component		Classification			Concentration
Phenol		Acute Tox. 3; Skin Corr. 1B; Eye Dam. 1; Muta. 2; STOT RE 2; Aquatic Chronic 2; H301, H331, H311, H314, H318, H341, H373, H411			= 100 %
CAS-No.	108-95-2				
EC-No.	203-632-7				
Index-No.	604-001-00-2	Concentration limits: >= 3 %: Skin Corr. 1B, H314; 1 - 3 %: Skin Irrit. 2, H315; 1 - 3 %: Eye Irrit. 2, H319;			

For the full text of the H-Statements mentioned in this Section, see Section 16.

3. Hazards Identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute toxicity, Oral (Category 3), H301
Acute toxicity, Inhalation (Category 3), H331
Acute toxicity, Dermal (Category 3), H311
Skin corrosion (Sub-category 1B), H314
Serious eye damage (Category 1), H318
Germ cell mutagenicity (Category 2), H341
Specific target organ toxicity - repeated exposure (Category 2), Nervous system, Kidney,
Liver, Skin, H373
Long-term (chronic) aquatic hazard (Category 2), H411
For the full text of the H-Statements mentioned in this Section, see Section 16.

Labelling according Regulation (EC) No 1272/2008

Signal Word Danger

Hazard Statements	H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled. H314 Causes severe skin burns and eye damage. H341 Suspected of causing genetic defects. H373 May cause damage to organs (Nervous system, Kidney, Liver, Skin) through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.
	P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Precautionary Statements	P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Supplemental Hazard Statements	None

Reduced Labeling (= 125 ml)

Signal Word	Danger
Hazard Statements	H341 Suspected of causing genetic defects. H314 Causes severe skin burns and eye damage.
	H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled.
Precautionary Statements	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
	P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Supplemental Hazard Statements	None
Other hazards	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. Vesicant., Rapidly absorbed through skin.

4. First Aid Measures

General advice	First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.
If inhaled	After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.
In case of skin contact	After contact with skin: rinse out with polyethylene glycol 400 or a mixture of polyethylene glycol 300/ethanol 2:1 and wash with plenty of water. If neither is available wash with plenty of water. Immediately take off contaminated clothing. Call a physician immediately.
In case of eye contact	After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.
If swallowed	If swallowed: give water to drink (two glasses at most). Seek medical advice immediately. In exceptional cases only, if medical care is not available within one hour, induce vomiting (only in persons who are wide awake and fully conscious), administer activated charcoal (20 - 40 g in a 10% slurry) and consult a doctor as quickly as possible. Do not attempt to neutralise.
Most important symptoms and effects, both acute and delayed	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Indication of any immediate medical attention and special treatment needed	No data available

5. Fire-fighting Measures

Suitable extinguishing media	Water Foam Carbon dioxide (CO2) Dry powder
Unsuitable extinguishing media	For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture	Carbon oxides Combustible. Vapors are heavier than air and may spread along floors. Forms explosive mixtures with air on intense heating. Development of hazardous combustion gases or vapours possible in the event of fire.
Advice for firefighters	Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.
Further information	Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Advice for non-emergency personnel: Avoid generation and inhalation of dusts in all circumstances. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.
Environmental Precaution	Do not let product enter drains.
Methods and materials for containment and cleaning up	Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully. Dispose of properly. Clean up affected area. Avoid generation of dusts.
Reference to other sections	For disposal see section 13.

7. Handling and Storage

Advice on safe handling	Work under hood. Do not inhale substance/mixture.
Advice on protection against fire and explosion	Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.
Hygiene measures	Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.
Storage conditions	Tightly closed. Dry. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.
Storage stability	Recommended storage temperature 2 - 8 °C Handle and store under inert gas. Light sensitive.
Storage class	Storage class (TRGS 510): 6.1A: Combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials
Specific end use(s)	Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. Exposure controls and personal protection

Ingredients with workplace control parameters

Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Worker DNEL, longterm	inhalation	Systemic effects	8 mg/m3
Worker DNEL, longterm	dermal	Systemic effects	

Predicted No Effect Concentration (PNEC)

Compartment	Value
Fresh water	0,0077 mg/l
Sea water	0,00077 mg/l
Fresh water sediment	0,0915 mg/kg
Sea sediment	0,00915 mg/kg
Soil	0,136 mg/kg
Sewage treatment plant	2,1 mg/l

Personal protective equipment

Eye/face protection	Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Full contact Material: Viton® Minimum layer thickness: 0,7 mm Break through time: 480 min
Skin protection	Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M) This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Splash contact Material: Viton® Minimum layer thickness: 0,7 mm Break through time: 480 min Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)
Body Protection	Flame retardant antistatic protective clothing. Recommended Filter type: Filter A-(P3)
Respiratory protection	The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.
Control of environmental exposure	Do not let product enter drains.

9. Physical and chemical properties

Physical state	Solid
Colour	No data available
Odour	Stinging
Melting point/freezing point	Melting point/range: 38 - 43 °C
Initial boiling point and boiling range	181,8 °C at 1.013 hPa
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	Upper explosion limit: 9,5 %(V) Lower explosion limit: 1,3 %(V)
Flash point	79,0 °C - closed cup
Autoignition temperature	715 °C at 1.013 hPa
Decomposition temperature	No data available
pH	6,0
Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: 3,437 Pas at 50,00 °C
Water solubility	87 g/l at 25 °C
Partition coefficient: n-octanol/water	log Pow: 1,47 at 30 °C - (ECHA), Bioaccumulation is not expected.
Vapor pressure	0,53 hPa at 20,0 °C
Density	1,13 g/cm ³ at 25 °C - DIN 51757
Relative density	No data available
Relative vapor density	No data available
Particle characteristics	No data available
Explosive properties	No data available
Oxidizing properties	No data available

10. Stability and reactivity

Reactivity	Forms explosive mixtures with air on intense heating. A range from approx. 15 Kelvin below the flash point is to be rated as critical. The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.
Chemical stability	The product is chemically stable under standard ambient conditions (room temperature) . Contains the following stabilizer(s): Hypophosphorous acid (0,15 %)
Possibility of hazardous reactions	Exothermic reaction with: Aluminum Aldehydes halogens hydrogen peroxide iron(III) compounds Oxidizing agents Strong acids Strong bases formaldehyde Risk of explosion with: nitrites nitrates salts of oxyhalogenic acids peroxi compounds
Conditions to avoid	Strong heating.
Incompatible materials	Rubber, various plastics, various alloys, various metals
Hazardous decomposition products	In the event of fire: see section 5

11. Toxicological information

Acute toxicity	Acute toxicity estimate Oral - 100,1 mg/kg (Calculation method) Acute toxicity estimate Oral - 100,1 mg/kg (Expert judgment) Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2) Acute toxicity estimate Inhalation - 4 h - 0,51 mg/l - dust/mist(Calculation method) Acute toxicity estimate Inhalation - 4 h - 0,51 mg/l - dust/mist (Expert judgment) Symptoms: Irritation, Lung edema Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2) Acute toxicity estimate Dermal - 660 mg/kg (Calculation method) LD50 Dermal - Rat - female - 660 mg/kg (OECD Test Guideline 402) Acute toxicity estimate Dermal - 660 mg/kg (Calculation method)
Skin corrosion/irritation	Skin - In vitro study Result: Causes burns. (OECD Test Guideline 431)
Serious eye damage/irritation	Eyes - Rabbit Result: Corrosive (OECD Test Guideline 405) Remarks: Causes serious eye damage. Risk of blindness!
Respiratory or skin sensitization	Sensitisation test: - Guinea pig Result: negative Remarks: (IUCLID)
Carcinogenicity	This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Germ cell mutagenicity	Suspected of causing genetic defects. Test Type: Mutagenicity (mammal cell test): chromosome aberration. Test system: Chinese hamster ovary cells Metabolic activation: Metabolic activation Method: OECD Test Guideline 473 Result: positive Test Type: Mutagenicity (mammal cell test): micronucleus. Test system: Chinese hamster ovary cells Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 487 Result: positive
Reproductive toxicity	No data available
Specific target organ toxicity - single exposure	No data available
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure. - Nervous system, Kidney, Liver, Skin Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)
Aspiration hazard	No data available
Additional Information	Product: Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, Circulatory collapse, tachypnea, paralysis, Convulsions, Coma., necrosis of mouth and G.I. Tract, Jaundice, respiratory failure, cardiac arrest To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

12. Ecological information

Toxicity

Toxicity to fish	Flow-through test LC50 - <i>Onchorhynchus clarki</i> - 8,9 mg/l - 96 h (US-EPA)
Toxicity to daphnia and other aquatic invertebrates	Static test EC50 - <i>Ceriodaphnia dubia</i> (water flea) - 3,1 mg/l - 48 h (US-EPA)
Toxicity to algae	Static test EC50 - <i>Pseudokirchneriella subcapitata</i> (algae) - 61,1 mg/l - 96 h (US-EPA)
Toxicity to bacteria	Static test IC50 - microorganisms - 21 mg/l - 24 h Remarks: (ECHA)
Toxicity to fish(Chronic toxicity)	Semi-static test NOEC - Fish - 0,077 mg/l - 60 d Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity)	Semi-static test NOEC - <i>Daphnia magna</i> (Water flea) - 0,16 mg/l - 16 d Remarks: (ECHA)
Persistence and degradability	Biodegradability aerobic - Exposure time 100 h Result: 62 % - Readily biodegradable. (OECD Test Guideline 301C) Bioaccumulation <i>Danio rerio</i> (zebra fish) - 5 h at 25 °C - 2 mg/l(Phenol) Bioconcentration factor (BCF): 17,5 (OECD Test Guideline 305) Remarks: Does not bioaccumulate.
Bioaccumulative potential	
Mobility in soil	No data available
Results of PBT and vPvB assessment	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. Product: Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Endocrine disrupting properties	
Other adverse effects	No data available

13. Disposal considerations

Waste treatment Methods	Product See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.
-------------------------	--

14. Transport information

UN number	ADR/RID: 1671	IMDG: 1671	IATA: 1671
UN proper shipping name	ADR/RID: PHENOL, SOLID	IMDG: PHENOL, SOLID	IATA: PHENOL, SOLID
Transport hazard class(es)	ADR/RID: 6.1	IMDG: 6.1	IATA: 6.1
Packaging group	ADR/RID: II	IMDG: II	IATA: II
Environmental hazards	ADR/RID: Yes	IMDG Marine pollutant : Yes	IATA: No
Special precautions for user	Tunnel restriction code : (D/E) Further information : No data available		

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture	This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.		
National legislation	Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : ENVIRONMENTAL HAZARDS		
Other regulations	Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable. Take note of Dir 94/33/EC on the protection of young people at work.		
Chemical Safety Assessment	A Chemical Safety Assessment has been carried out for this substance.		

16. Other information

Other Information	The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if RX Marine International has been advised of the possibility of such damages. DISCLAIMER OF LIABILITY : The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.
-------------------	---