

Material Safety Data Sheet

Anti Cracking H2S Corrosion Inhibitor (RXSOL-81-2065-210)



1. Product and Company Identification

Product Name Anti Cracking H2S Corrosion Inhibitor

Part Number RXSOL-81-2065-210

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Muscat, Fujairah, Nairobi, Kolkata, Vizag, Chennai, Gandhidham, Canada

Phone +91 22 27815540 / 41 / 42

Fax +91 22 2781 1318 :: AOH :0091 9821214367

Email mail@rxmarine.com

2. Composition / information on ingredients

Ingredient name	Weight %	CAS number
Petroleum Naphtha	50 - 60	64742-47-8
Amine Derivative	10 - 20	Trade secret.
Ethylbenzene	10 - 20	100-41-4
Acid phosphate ester	1 - 5	Trade secret.
Amine derivative	1 - 5	Trade secret.
Isopropanol	1 - 5	67-63-0
Heavy aromatic naphtha	1 - 5	64742-94-5
Toluene	0.1 - 1	108-88-3
Xylene	1 - 5	1330-20-7
Polyoxyalkylenes	0.1 - 1	Trade secret.
Cumene	0.1 - 1	98-82-8

3. Hazards Identification

Signal word

Danger

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Hazard statements

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure. (hearing organs)

Harmful to aquatic life with long lasting effects.

Precautionary statements	Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
		Wear protective gloves: > 8 hours (breakthrough time): Rubber gloves. Nitrile gloves. Neoprene gloves. Wear protective clothing.
		Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Keep container tightly closed.
Precautionary statements	Response	Avoid release to the environment. Do not breathe vapor. Wash thoroughly after handling.
		IF exposed or concerned: Get medical advice or attention.
		IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
		IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention.
Storage		IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Disposal		Store locked up. Store in a well-ventilated place. Keep cool.
		Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements		Avoid contact with skin and clothing. Wash thoroughly after handling.
Hazards classified	not otherwise	Prolonged or repeated contact may dry skin and cause irritation.

4. First Aid Measures

Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Continue to rinse for at least 10 minutes. Check for and remove any contact lenses. Get medical attention.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.
Most important symptoms/effects, acute and delayed	Eye contact: Causes serious eye irritation.
	Inhalation: No known significant effects or critical hazards.
	Skin contact: Causes skin irritation. Defatting to the skin.
	Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms	Eye contact: Adverse symptoms may include the following: pain or irritation, watering, redness.
	Inhalation: reduced fetal weight, increase in fetal deaths, skeletal malformations
	Skin contact: irritation, redness, dryness, cracking, reduced fetal weight, increase in fetal deaths, skeletal malformations
	Ingestion: Adverse symptoms may include the following: reduced fetal weight, increase in fetal deaths, skeletal malformations

5. Fire-fighting Measures

Suitable extinguishing media	Use dry chemical, CO2, alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	Carbon dioxide, Carbon monoxide, Nitrogen oxides, Phosphorus oxides
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental Release Measures

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
Methods and materials for containment and cleaning up- Small spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Methods and materials for containment and cleaning up - Large spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and Storage

Protective measures	Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a segregated and approved area. Store in a dry, cool and well-ventilated area. Store in original container, protected from direct sunlight. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

8. Exposure controls and personal protection

Appropriate engineering controls	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	Wear chemical safety goggles. When transferring material wear face-shield in addition to chemical safety goggles.
Hand protection	Chemical-resistant gloves: Rubber gloves. Nitrile gloves. Neoprene gloves.
Skin protection	Wear long sleeves to prevent repeated or prolonged skin contact.
Respirator protection	If a risk assessment indicates it is necessary, use a properly fitted, air purifying or supplied air respirator complying with an approved standard. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

9. Physical and chemical properties

Physical state	Liquid.
Color	Amber.
Odor	Aromatic.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-17.8°C (-0.04°F)
Initial Boiling Point	Not available.
Boiling point, initial boiling point, and boiling range	146°C (294.8°F)

Flash point	Closed cup: 26.7°C (80.1°F)
Burning time	Not applicable.
Burning rate	Not applicable.
Evaporation rate	Not applicable.
Flammability	Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat.
Lower and upper limit/flammability limit explosion	Not applicable.
Vapor pressure	Not applicable.
Relative vapor density	Not applicable.
Relative density	0.93
Density	7.76 (lbs/gal)
Solubility in water	Not applicable.
Partition coefficient: noctanol/water	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not applicable.
Viscosity	Not applicable.
VOC	Not applicable.
Pour Point	Not applicable.

10. Stability and reactivity

Reactivity	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials, reducing materials and acids.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Irritation/Corrosion	No available toxicity data.
Sensitization	No available toxicity data.
Mutagenicity	No available toxicity data.
Carcinogenicity	No available toxicity data.
Reproductive toxicity	No available toxicity data.
Teratogenicity	No available toxicity data.
Carcinogenicity	Reasonably anticipated to be a human carcinogen.
Specific target organ toxicity (single exposure)	Respiratory tract irritation
Specific target organ toxicity (repeated exposure)	Hearing organs
Information on the likely routes of exposure	Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects	Eye contact: Causes serious eye irritation.
	Inhalation: No known significant effects or critical hazards.
	Skin contact: Causes skin irritation. Defatting to the skin.
Symptoms related to the physical, chemical and toxicological characteristics	Ingestion: No known significant effects or critical hazards.
	Eye contact: Adverse symptoms may include the following: pain or irritation, watering, redness
	Inhalation: reduced fetal weight, increase in fetal deaths, skeletal malformations Skin contact: irritation, redness, dryness, cracking, reduced fetal weight, increase in fetal deaths, skeletal malformations Ingestion: Adverse symptoms may include the following: reduced fetal weight, increase in fetal deaths, skeletal malformations
Delayed and immediate effects and also chronic effects from short and long term exposure	Not available.

12. Ecological information

Persistence and degradability	Not available.
Mobility in soil	Not available.
Other adverse effects	No known significant effects or critical hazards.

13. Disposal considerations

Disposal methods	Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
------------------	---

14. Transport information

UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Contains: Petroleum naphtha, Ethylbenzene)
Transport hazard class(es)	3
Packaging group	III
Environmental hazards	No

15. Regulatory information

Safety, health and environmental regulations specific for the product in question	This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
Other regulations	No data available
Chemical Safety Assessment	For this product a chemical safety assessment was not carried out.

16. Other information

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchant ability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if RX Marine International has been advised of the possibility of such damages.

Other
Information

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.